

# McCloskey 516RT Trommel Specifications



## HIGH PERFORMANCE TROMMEL

Larger producers can achieve high quality fine materials with the McCloskey 516 Trommel. McCloskey International offers a wide range of drum designs and screen sizes to improve quality and meet high demand.

Material such as topsoil, compost, sand and gravel, wood chip, and recycling materials spend more time in the sixteen foot drum for better screening results.

The three screen sections allow for flexibility in sizing to maximise productivity, while the hydraulically folding end conveyor allows oversize material to be effectively stockpiled.

For heavy duty applications, a remote control hydraulic tipping grizzly can be added to scalp off large material.

## 516RT

Engine	100 hp (75 kW) Diesel
Transport Height	11' 8" (3.56m)
Transport Length	50' 11" (15.51m)
Transport Width	8' 11" (2.72m)
Weight	50,000 lb (22,680kg)
Radial Stockpile Height	12' 11" (3.94m)
Oversize Stockpile Height	8' 7" (2.62m)
Drum	5'x16' (1.52mx4.88m)

### OVERSIZE CONVEYOR

Heavy duty oversize conveyor at the end of the trommel offers adjustable speed and stockpile height.



### TEDD PANEL UNIVERSAL DISPLAY

The control panel provides an intuitive, icon-based user interface, which allows all functions to be controlled and monitored.

### HOPPER CAPACITY

Hopper capacity of 4.5-7.0yd<sup>3</sup> with extensions for greater efficiency.



### TROMMEL DRUM

Features a 5 feet by 16 feet steel drum, with numerous drum and screen options available.

### BRUSHES

Ground level adjustable brushes keep the screen clean and rotate away from drum for ease of drum change.



### RADIAL CONVEYOR

RT/RE models include a remote controlled radial conveyor with 180° swing and variable discharge height for maximum stockpiling flexibility.